



Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

DESCRIPTION

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

DIMENSIONS AND WEIGHT

External Dimensions (l x w x h) [mm] [inch]		Internal Dimensions ¹ (d x h) [mm] [inch]		Tolerances [mm] [inch]	
380 x 360 x 375	15 x 14.2 x 14.8	x 200	0 x 7.9	± 5	± 0.2
Tare Weight ¹ [kg]		Payload ¹ (Volume) [L]			
9 ± 1	19.8 ± 2.2			8	

¹including Temperature Batteries

TEMPERATURE BATTERY CONFIGURATION

OneBlok	Pieces	Dimensions ² (l x w x h) [mm] [inch]	Weight [kg] [lbs]		Material number
23233	6	232 x 232 x 33 9.1 x 9.1 x 1.3	1	2.2	AK000477

²dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

PERFORMANCE The OnePak 8 +22G EL is qualified in the temperature range from +15 °C to +25 °C

Temperature scenario	Duration [hrs]	Kelvin-hours ³	Average ambient temperature [°C]
ISTA 7D summer	≥ 107	≥ 1081	+30.1
ISTA 7D winter	≥ 119	≤ -1809	+4.8

³Detailed information about the concept of Kelvin-hours on www.kelvinhours.com

For more details, please view the qualification report. Before performing a shipment with the OnePak 8 +22G EL it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact support@envirotainer.com.