



Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

## DESCRIPTION

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

## DIMENSIONS AND WEIGHT

External Dimensions (l x w x h) [mm] [inch]		Internal Dimensions <sup>1</sup> (d x h) [mm] [inch]		Tolerances [mm] [inch]	
480 x 460 x 385	18.9 x 18.1 x 15.2	x 220	0 x 8.7	± 5	± 0.2

Tare Weight <sup>1</sup> [kg] [lbs]		Payload <sup>1</sup> (Volume) [L]	
12 ± 1	26.5 ± 2.2		23

<sup>1</sup>including Temperature Batteries

## TEMPERATURE BATTERY CONFIGURATION

OneBlok	Pieces	Dimensions <sup>2</sup> (l x w x h) [mm] [inch]		Weight [kg] [lbs]		Material number
34242	4	342 x 250 x 23	13.5 x 9.8 x 0.9	1.3	2.9	AK000478
34342	2	342 x 342 x 23	13.5 x 13.5 x 0.9	1.5	3.3	AK000479

<sup>2</sup>dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

## PERFORMANCE The OnePak 23 +22G EL is qualified in the temperature range from +15 °C to +25 °C

Temperature scenario	Duration [hrs]	Kelvin-hours <sup>3</sup>	Average ambient temperature [°C]
ISTA 7D summer	≥ 118	≥ 1204	+30.2
ISTA 7D winter	≥ 119	≤ -1809	+4.8

<sup>3</sup>Detailed information about the concept of Kelvin-hours on [www.kelvinhours.com](http://www.kelvinhours.com)

For more details, please view the qualification report. Before performing a shipment with the OnePak 23 +22G EL it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact [support@envirotainer.com](mailto:support@envirotainer.com).