



Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

DESCRIPTION

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

DIMENSIONS AND WEIGHT

External Dimensions (l x w x h) [mm] [inch]		Internal Dimensions ¹ (d x h) [mm] [inch]		Tolerances [mm] [inch]	
1200 x 800 x 820	47.2 x 31.5 x 32.3	x 475	0 x 18.7	± 5	± 0.2

Tare Weight ¹ [kg] [lbs]		Payload ¹ (Volume) [L]	
66.9 ± 2	147.5 ± 4.4		298

¹including Temperature Batteries

TEMPERATURE BATTERY CONFIGURATION

OneBlok	Pieces	Dimensions ² (l x w x h) [mm] [inch]		Weight [kg] [lbs]		Material number
34242	20	342 x 250 x 23	13.5 x 9.8 x 0.9	1.3	2.9	AK000478
44342	4	442 x 342 x 23	17.4 x 13.5 x 0.9	2	4.4	AK000480

²dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

PERFORMANCE The OnePak 300 +22G EL is qualified in the temperature range from +15 °C to +25 °C

Temperature scenario	Duration [hrs]	Kelvin-hours ³	Average ambient temperature [°C]
ISTA 7D summer	≥ 141	≥ 1382	+29.8
ISTA 7D winter	≥ 126	≤ -1915	+4.8

³Detailed information about the concept of Kelvin-hours on www.kelvinhours.com

For more details, please view the qualification report. Before performing a shipment with the OnePak 300 +22G EL it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact support@envirotainer.com.