ProofTainer Euro +05G (excl. floor grid)

[va-Q-tainer EUROx +05G (excl. floor grid)]

For +2 °C to +8 °C shipments

Envirotainer°
Precision with Purpose



DESCRIPTION

Delivering superior performance while streamlining handling, the ProofTainer family features six sizes, accommodating from 0.5 – 2 EU or 1 - 2 US pallets. Whether you're shipping clinical trials or commercial drugs, we ensure consistent temperature control throughout your products journey. With qualified temperature ranges from -70°C to +20°C and over 120 hours of autonomy, ProofTainer provides optimal conditions for your sensitive cargo, delivering the flexibility you need for your product requirements.

Envirotainer AB
Staffans väg 2A | SE-192 78 Sollentuna | Sweden
Tel.: +46 8 586 29 300 | www.envirotainer.com

ProofTainer Euro +05G (excl. floor grid)

[va-Q-tainer EUROx +05G (excl. floor grid)]

For +2 °C to +8 °C shipments

Envirotainer°
Precision with Purpose

DIMENSIONS AND WEIGHT

External Dimensions (l x w x h)		Internal Dimensions[1] (l x w x h)		Tolerances	
[mm]	[inch]	[mm]	[inch]	[mm]	[inch]
1423 x 1093 x 1580	56 x 43 x 62.2	1200 x 850 x 1220	47.2 x 33.5 x 48	± 8	± 0.3

Tare Weight[1]		Volumetric weight		Maximum Payload (Weight)		Payload[1] (Volume)
[kg]	[lbs]	[kg]	[lbs]	[kg]	[lbs]	[L]
453 ± 20	998.7 ± 44.1	410	903.9	500	1102.3	1244

[1]including Temperature Batteries

TEMPERATURE BATTERY CONFIGURATION

ProofBlok	Pieces	Dimensions[2] (l x w x h)		Weight		Material number
		[mm]	[inch]	[kg]	[lbs]	
27L +05G	36	470 x 275 x 32	18.5 x 10.8 x 1.3	3	6.6	AK000295

[2]dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

PERFORMANCE The ProofTainer Euro +05G (excl. floor grid) is qualified in the temperature range from +2 °C to +8 °C

Temperature scenario	Duration [hrs]	Kelvin-hours[3]	Average ambient temperature [°C]
regular summer	≥ 94	≥ 2369	+30.2
regular winter	≥ 144	< -749	-0.2
extreme summer	46	n.a.	+50.2
extreme winter	31	n.a.	-20.2

[3]Detailed information about the concept of Kelvin-hours on www.kelvinhours.com

For more details, please view the qualification report. Before performing a shipment with the ProofTainer Euro +05G (excl. floor grid) it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact support@envirotainer.com.

Envirotainer AB
Staffans väg 2A | SE-192 78 Sollentuna | Sweden
Tel.: +46 8 586 29 300 | www.envirotainer.com